

SAGINAW COUNTY ROAD COMMISSION

BID FORM

Gentlemen/Ladies:

Sealed Proposals will be received at the office of the Board of Saginaw County Road Commissioners at 3020 Sheridan Avenue, Saginaw, Michigan, 48601, until:

Thursday, December 19, 2024 at 10:00 a.m.

At which time and place proposals will be publicly opened and read for the furnishing of the following supplies, materials, and/or services for delivery at

3110 Sheridan Avenue, Saginaw, MI 48601

Dan Medina
Director of Maintenance

Proposal No. 14 – CS-T© – Trap Rock

SPECIFICATIONS: Must meet M.D.O.T. standard specifications for CS-T©. All material delivered shall be dry. (Wet material will be refused.)

BID PERIOD: April 1, 2025, to March 31, 2026 Price to be firm for bid period.

SEE ATTACHED SHEET for prices, quotations, sign specifications and sizes.

In compliance with the above invitation for proposals, and subject to all conditions thereof, the undersigned offers, and agrees if this bid be accepted within 15 days from the date of opening, to furnish any and all items at the price quoted opposite each item, F.O.B. as indicated.

Specification:

Description:	CS-T©	Unit	Unit Price
Chesaning garage - (700 Lansing St., Chesaning, MI 48616)	material and trucking	TON	\$ _____
Hemlock garage - (330 Cedar St., Hemlock, MI 48626)	material and trucking	TON	\$ _____
Saginaw garage - (3110 Sheridan Ave., Saginaw, MI 48601)	material and trucking	TON	\$ _____
Geddes Road pit - (11504 Geddes Rd, Saginaw, MI 48609)	material and trucking	TON	\$ _____
Curtis Road pit - (4800 E. Curtis Rd., Bridgeport, MI 48722)	material and trucking	TON	\$ _____
Chesaning salt shed - (1777 W Brady Rd, Chesaning, MI 48616)	material and trucking	TON	\$ _____

BIDDER: _____

ADDRESS: _____

CITY, STATE, and ZIP: _____

TERMS: Net 30 **DELIVERY:** _____

BY: _____ **TITLE:** _____

DATE: _____ **PHONE #:** _____

INDICATE ON ENVELOPE: **PROPOSAL NUMBER**
BID ITEM
TIME and DATE

For further inquiries please contact:
Dan Medina, Director of Maintenance,
989-399-3773

SPECIFICATIONS

Aggregates

Aggregates shall consist of sound, tough, durable particles, free from adherent films of matter that would prevent thorough coating with the bituminous material. The percentage of wear shall not be greater than 45 percent when tested in accordance with ASTM C-131.

Aggregates shall contain 100 percent having at least one fractured face.

Sampling and Testing

ASTM D75 shall be used in sampling the aggregate. The Contractor shall furnish documentation to the Engineer, at the time of bid confirming that the aggregate meets both AWI and L.A. Abrasion specification requirements.

Sources of Aggregates

Sources of aggregates shall be selected well in advance of the time the materials are required on the work site. When the aggregates are obtained from a previously approved source of an existing source producing aggregates that have a satisfactory service submitted 10 days prior to the start of construction. The Engineer will make an inspection of the producer's operation. Approval of the source of aggregate does not relieve the Contractor in any way of the responsibility for delivery at the job site of aggregates that meet the requirements specified herein.

Samples of Aggregates

Saginaw County Road Commission shall take samples of aggregate during the time of delivery. All samples taken will be required to meet the following requirements:

Capital Preventive Maintenance Final Aggregate Blend Gradation Requirements

TABLE 1 CS-T© - Trap Rock

Sieve Size	Percentage by Weight Passing Sieves Surface Course
1/2"	100
3/8"	100
1/4"	85-100
NO.8	0-15
PAN	2% Max